



LM-79 DLC IK10 IP66



Modèle	ECLLD35H	ECLLD65H	ECLLD100H	ECLLD135H	ECLLD165H	ECLLD200H	ECLLD230H
Puissance Nominale (W)	35	65	100	135	165	200	230
Equivalent Remplacement HID (W)	70	100	150	250	> 250	400	> 400
Alimentation	240V, 50 Hz						
Driver Led	Meanwell Série HLG						
Source Led	Philips LUXEON Rebel ES						
Flux Lumineux lm (+/-5%)	3 850	6 825	9 500	12 825	17 325	21 000	24 150
Température de couleur CCT							
Types Focales							
Indice IRC	Minimum 70						
Maintenance lumen	>67000 heures -L70, @25°C						
Température d'utilisation	-40 à 50°C						
Garantie	5 ans						
Matériaux	Corps en aluminium, Lentilles en Polycarbonate						
Indices de protection	IP 66, IK 08						
Couleur							
Ouverture pour fixation tube	Ø 60 mm						
Inclinaison de la tête	Installation Horizontale : 0, 10, 15°			Installation Verticale : 0, 5, 15°			
Dimensions (mm)	431 x 316 x 136	540 x 316 x 136	577 x 316 x 136	650 x 316 x 136	723 x 316 x 136	796 x 316 x 136	869 x 316 x 136
Poids (kg)	5.3	6.1	7.3	8.2	9.0	9.9	10.8